(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

madonal Durcau



(43) International Publication Date 7 April 2005 (07.04.2005)

PCT

(10) International Publication Number WO 2005/031596 A1

(51) International Patent Classification⁷: G06F 17/14

(21) International Application Number:

PCT/SG2004/000121

(22) International Filing Date: 6 May 2004 (06.05.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/507,440 60/507,210 29 September 2003 (29.09.2003) US 29 September 2003 (29.09.2003) US


- (71) Applicant (for all designated States except US): AGENCY FOR SCIENCE, TECHNOLOGY AND RESEARCH [SG/SG]; 20 Biopolis Way, #07-01 Centros, Singapore 138668 (SG).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HUANG, Haibin

[CN/SG]; Blk 354B, Admiralty Drive, #06-244, Singapore 752354 (SG). LIN, Xiao [SG/SG]; Block 117, Bt Batok West Avenue 6, #18-238, Singapore 650117 (SG). RA-HARDJA, Susanto [ID/SG]; 10A Braddell Hill, #22-02, Singapore 579720 (SG). YU, Rongshan [CN/SG]; Block 168, Boon Lay Drive, #07-621, Singapore 640168 (SG).

- (74) Agent: VIERING, JENTSCHURA & PARTNER; Rochor Post Office, Rochor Road, P.O. Box 1088, Singapore 911833 (SG).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: METHOD FOR TRANSFORMING A DIGITAL SIGNAL FROM THE TIME DOMAIN INTO THE FREQUENCY DOMAIN AND VICE VERSA



(57) Abstract: A method for transforming a digital signal from the time domain into the frequency domain and vice versa using a transformation function comprising a transformation matrix, the digital signal comprising data symbols which are grouped into a plurality of blocks, each block comprising a predefined number of the data symbols. The method includes the process of transforming two blocks of the digital signal by one transforming element, wherein the transforming element corresponds to a block-diagonal matrix comprising two sub matrices, wherein each sub-matrix comprises the transformation matrix and the transforming element comprises a plurality of lifting stages and wherein each lifting stage comprises the processing of blocks of the digital signal by an auxiliary transformation and by a rounding unit.

WO 2005/031596 A1

TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.